

BLOWER PANEL

BP-031B(301H)


■DESCRIPTION

Designed exclusively for use with TOA's component racks, the BP-031B blower unit forcibly cools amplifiers or other equipment to protect them against heat that can be generated from within the component racks. It is equipped with a 3-position switch (MANUAL-OFF-AUTO).

■ SPECIFICATIONS

| Power Source | 220 V AC, 50/60 Hz |
|---------------------|--|
| Power Consumption | 8.5 W |
| Control | 3-position switch (MANUAL/OFF/AUTO) |
| Protection | 1 AC Fuse |
| Automatic Operation | Thermal Switch ON |
| Ĭ . | (When rack temperature exceeds +48 °C (118.4 °F)) |
| | Thermal Switch OFF |
| | (When rack temperature drops below +38 °C (100.4 °F)) |
| Ventilation | 1.5 m³/min. |
| Finish | Panel: Surface—treated steel plate, black, 30 % gloss, paint |
| Dimensions | 483 (W) × 133 (H) × 152.7 (D) mm (19.02" × 5.24" × 6.01") |
| Weight | 3.7 kg (8.16 lb) |
| Accessory | Rack mounting screw (with washer)4, Fuse1, |
| | Power cord (2 m (6.56 ft))1 |

APPEARANCE



Rear View

